



**ApcoBuild**<sup>TM</sup>  
Build Smarter

# ANTI-HACK<sup>TM</sup>

**SPECIALITY POLYMER LATEX THAT  
ELIMINATES NEED FOR HACKING**

- Eliminates need for Hacking. Thus saves on effort and labour cost
- Avoids damage to structure
- Suitable for interior and exterior application
- Provides excellent bonding between plaster (mortar/gypsum) and concrete
- Economical in use

---

ApcoBuild Anti-Hack is specially formulated and designed to avoid the need for hacking, before taking up mortar plaster and gypsum plaster over new or old concrete.

## AREAS OF APPLICATION

- All concrete surface required to be plastered

## ADVANTAGES

- Eliminates need for Hacking. Thus saves on effort and labour cost
- Avoids structure from damage
- Suitable for interior and exterior application
- Provides excellent bonding between plaster (mortar/gypsum) and concrete
- Economical in use

## APPLICATION METHOD

### SURFACE PREPARATION

- Concrete surface for treatments must be thoroughly cleaned of all laitance, loose materials, oils, grease etc.

### APPLICATION OF MORTAR PLASTER

- Moisten the surface with clean water and allow excess surface water to evaporate
- Apply single coat of ApcoBuild Anti-Hack by brush/roller or spray on pretreated surface
- When the bond coat becomes tacky, apply the chat coat (dash coat) of plaster
- Allow the chat coat dash coat to dry for 24 hours and then apply the plaster to finish work.

### APPLICATION OF GYPSUM PLASTER

- Moisten the surface with clean water and allow excess surface water to evaporate
- Apply single coat of ApcoBuild Anti-Hack by brush/roller or spray on pretreated surface
- When the bond coat becomes tacky, apply the gypsum plaster with trowel to desire thickness

## PRECAUTIONS AND LIMITATIONS

- ApcoBuild Anti-Hack must be applied as neat coat
- Never mix it with cement or add water
- Gypsum should be placed on tacky condition. If it dries, apply second coat to reach the tacky state

## TECHNICAL INFORMATION

Test Parameters	Specification
Appearance	Milky White Liquid
Specific Gravity	1.00 ± 0.005
Coverage	90 to 100 Sqft. per kg for single coat (May vary with substrate condition)

## SHELF LIFE

12 months.

## PACKAGING

1, 5 & 26 kg.

## HEALTH AND SAFETY

Recommended use of hand gloves, goggles & masks. In case of eye or skin contamination, wash well with soap & cold water. Seek medical advice as necessary.

**DISCLAIMER:** These suggestions and data are based on information, which we believe to be reliable. They are given for information only and in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the user determine the suitability of our materials and suggestions before adopting them on a commercial scale.

Recommended use in construction segment.



## apcotex industries limited

Plot No. 3/1, MIDC Industrial Area, Taloja-410 208, Dist-Raigad, India

Tel : +91-22-2740-3500 Fax : +91-22-2741-2052

Email : apcobuild@apcotex.com Website : www.apcobuild.co.in