





APCOBUILD GYPBIND

SPECIALITY FORMULATED POLYMER LATEX THAT ELIMINATES NEED FOR HACKING

- Eliminates need for hacking, Thus saves on effort and labour cost
- Avoids damage to concrete structure
- Suitable for interior and exterior application
- Provides excellent bonding between Gypsum plaster and Concrete.
 Also can be recommended on light weight concrete block and bricks surface.
- Economical in use

APCOBUILD GYPBIND is a specially formulated and designed to avoid the need for hacking, before taking up gypsum plaster over new or old concrete structure.

ADVANTAGES

- Eliminates need for hacking. Thus saves on effort and labor cost
- Avoids damage to concrete structure
- Suitable for interior and exterior application
- Provides excellent bonding between Gypsum plaster and concrete
- Economical in use

APPLICATION METHOD

SURFACE PREPARATION

Concrete surface for treatment must be thoroughly cleaned of all laitance, loose materials, oils, grease etc.

APPLICATION OF GYPSUM PLASTER

Apply single coat of ApcoBuild Gypbind by brush or roller on pretreated surface and allow to dry as required. After dried completely apply the gypsum plaster with trowel to desire thickness

PRECAUTIONS AND LIMITATIONS

- ApcoBuild Gypbind must be applied as neat coat
- · Never mix it with cement or add water in to it
- Stir well before use

TECHNICAL INFORMATION

Properties	Specification
Appearance	Green colour paste with sand
рН	9 ± 00 0.50
%NVM	45 ± 00 4.0
Viscocity RVT(7,20)cps	25,000 to 30,000 cps
Specific gravity	1±06 0.04
Coverage(sq ft/kg)*	50.0 – 55.0
Brushability	Easy to brush

^{*} Coverage may vary depend on surface

SHELF LIFE

6 months in original, unopened palletised containers, stored in well ventilated, dry conditions.

PACKAGING

30kg

HEALTH AND SAFETY

Keep out of reach of children.

Keep in cool place. If in contact with eyes, rinse with plenty of water and seek medical attention if irritation develops. If in contact with skin, wash immediately with plenty of soap and water.

DISCLAIMER: These suggestions and data are based on information, which we believe to be reliable. They are given for information only and in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the user determine the suitability of our materials and suggestions before adopting them on a commercial scale.

Recommended use in construction segment.



apcotex industries limited

Plot No. 3/1, MIDC Industrial Area, Taloja-410 208, Dist-Raigad, India

Tel: +91-22-2740-3500 Fax: +91-22-2741-2052

Email: apcobuild@apcotex.com Website: www.apcobuild.co.in